

DISPLAYPORT -VGA/DVI/HDMI CABLE TYPE

- Feature**
- DisplayPort 1.1 compliant receiver offering 5.4Gbps over 2 lanes.
 - Support full DisplayPort link training.
 - Encrypted HDCP key storage using on-board memory or optional external EEPROM
 - ESD protect: Human Body Mode at 8 kV, Machine Mode at 400 V, and Charged Device Mode at 2 kV.
 - PC: VGA, SVGA, VGA, SXGA, UXGA and UXGA.



www.pcidv.com

Item	Convertor
DisplayPort source input port	1
Video device output port	1
DisplayPort source port connector (female)	DisplayPort 20 pin
Video device port connector (male)	VGA 15 pin (D-SUB)
Video band width (bps)	5.7G link
Single link range	UXGA
Vertical frequency range	60Hz
Operation temperature	0~50°C
Storage temperature	-40~85°C
Emission	CE, FCC, C-Tick
Enclosure	Plastic

- Feature**
- Compliant with DisplayPort 1.1 specification for both 1.62 and 2.7 Gbps.
 - Support full DisplayPort link training.
 - Compliant with DVI 1.1 specification up to 1.65 Gbps.
 - ESD protect: Human Body Mode at 8 kV, Machine Mode at 400V, and Charged Device Mode at 2 kV.
 - PC: VGA, SVGA, XGA, SXGA, and UXGA.
 - HDTV: 480i, 576i, 480p, 576p, 1080i and 1080p.
 - Standby mode current: 64uA.



www.pcidv.com

Item	Convertor
DisplayPort source input port	1
Video device output port	1
DisplayPort source port connector (female)	DisplayPort 20 pin
Video device port connector (male)	DVI 24 pin
Video band width (bps)	2.7G single link
Single link range	1080P/UXGA
Vertical frequency range	60Hz
Operation temperature	0~50°C
Storage temperature	-20~60°C
Emission	CE, FCC, C-Tick
Enclosure	Plastic

- Feature**
- Compliant with DisplayPort 1.1 specification for both 1.62 and 2.7 Gbps.
 - Support full DisplayPort link training.
 - Compliant with HDMI 1.3a specification up to 2.25 Gbps.
 - ESD protect: Human Body Mode at 8 kV, Machine Mode at 400V, and Charged Device Mode at 2 kV.
 - PC: VGA, SVGA, XGA, SXGA, and UXGA.
 - HDTV: 480i, 576i, 480p, 576p, 1080i and 1080p.
 - Standby mode current: 64uA.



www.pcidv.com

Item	Convertor
DisplayPort source input port	1
Video device output port	1
DisplayPort source port connector (female)	DisplayPort 20 pin
Video device port connector (male)	HDMI 19 pin
Video band width (bps)	2.7G single link
Single link range	1080P/UXGA
Vertical frequency range	60Hz
Operation temperature	0~50°C
Storage temperature	-20~60°C
Emission	CE, FCC, C-Tick
Enclosure	Plastic