

**1 DISPLAYPORT-HDMI ADAPTER ASS'Y TYPE**

- . Compliant with DisplayPort Interoperability specification V1.1a.
- . Support full DisplayPort link training.
- . Compliant with HDMI 1.3a specification up to 2.25 Gbps.
- . ESD protect: Human Body Mode at 8 kV, Machine Mode at 400V, and Charged Device Mode at 2 kV.
- . PC: VGA, SVGA, XGA, SXGA, and UXGA.
- . HDTV: 480i, 576i, 480p, 576p, 1080i and 1080p.
- . Standby mode current: 64uA.
- . LED indicator: Cable link status.



1

**2 DISPLAYPORT-DVI ADAPTER ASS'Y TYPE**

- . Compliant with DisplayPort Interoperability specification V1.1a.
- . Support full DisplayPort link training.
- . Compliant with DVI 1.1 specification up to 1.65 Gbps.
- . ESD protect: Human Body Mode at 8 kV, Machine Mode at 400V, and Charged Device Mode at 2 kV.
- . PC: VGA, SVGA, XGA, SXGA, and UXGA.
- . HDTV: 480i, 576i, 480p, 576p, 1080i and 1080p.
- . Standby mode current: 64uA.
- . LED indicator: Cable link status.



2

**3 DISPLAYPORT-HDMI ADAPTER MOLDING TYPE**

- . Compliant with DisplayPort Interoperability specification V1.1a.
- . Support full DisplayPort link training.
- . Compliant with HDMI 1.3a specification up to 2.25 Gbps.
- . ESD protect: Human Body Mode at 8 kV, Machine Mode at 400V, and Charged Device Mode at 2 kV.
- . PC: VGA, SVGA, XGA, SXGA, and UXGA.
- . HDTV: 480i, 576i, 480p, 576p, 1080i and 1080p.
- . Standby mode current: 64uA.
- . LED indicator: Cable link status.



3

**4 DISPLAYPORT-DVI ADAPTER MOLDING TYPE**

- . Compliant with DisplayPort Interoperability specification V1.1a.
- . Support full DisplayPort link training.
- . Compliant with DVI 1.1 specification up to 1.65 Gbps.
- . ESD protect: Human Body Mode at 8 kV, Machine Mode at 400V, and Charged Device Mode at 2 kV.
- . PC: VGA, SVGA, XGA, SXGA, and UXGA.
- . HDTV: 480i, 576i, 480p, 576p, 1080i and 1080p.
- . Standby mode current: 64uA.
- . LED indicator: Cable link status.



4